



side¥-ick

The compact, by-your-side, all-in-one scanner.







Everything you need for desktop document management, all in one box.

| Scanning Mode | | Duplex | | | |
|---|------------------------------------|--|-----------------------|--|-----------------------|
| Scanning Speed Binary 200 dpi Letter Size Portrait | | Simplex 23 ppm (pages per minute) Duplex 42 ipm (images per minute) | | Simplex 43 ppm (pages per minute) Duplex 76 ipm (images per minute) | |
| | Color 200 dpi | Simplex 8 ppm Duplex 14 ipm | | Simplex 14 ppm Duplex 24 ipm | |
| Resolution | | 100-600 dpi, Color (with VRS) 100-400 dpi Optical: 600 dpi | | | |
| Output Options | | Bitonal, Grayscale (8 bit), and Color (24 bit) | | | |
| Image Enhancement | | VRS 4.1 Basic Image Enhancement for Auto Cropping, Deskew, Brightness and Contrast Control | | | |
| Document Size | | 2.0 x 2.8 in. (50.8 x 70 mm) to 8.5 x 14 in. (216 x 356 mm), Up to 8.5 x 25 in. (216 x 635mm)* | | | |
| Paper Thickness | | Single Paper Feeding: 2.0 to 5.9 mils (0.05 to 0.15 mm) Continuous Paper Feeding: 2.36 to 5.9 mils (0.06 to 0.15 mm) Note: 1 mil = 1/1000 in. | | | |
| Paper Weight | | Single Paper Feeding: 10.7 to 33.9 lbs. Continuous Paper Feeding: 13.3 to 33.9 lbs. | | | |
| Interface | | USB 2.0. (cable included) and SCSI III (50 pin) | | | |
| Feeder Capacity | | 120 Sheets | | | |
| Scanner Size | | 14 x 12.5 x 9.25 in. (35.5 x 32 x 24.1 cm) With Tray Extended: 14 x 19.75 x 10.6 in. (35.5 x 50 x 27 cm) | | | |
| Scanner Weight | | 18.7 lbs (8.5 kg) | | 20.1 lbs (9.1 kg) | |
| Power Requirements | | AC 100-120 V 50/60 Hz | AC 220-240 V 50/60 Hz | AC 100-120 V 50/60 Hz | AC 220-240 V 50/60 Hz |
| Energy Efficient Power Consumptions | Maximum (Scanning) | 37 W | 38 W | 50 W | 50 W |
| | Minimum (Standby) | 17 W | 19 W | 18 W | 19 W |
| energy | Sleep Mode | 6 W | 8 W | 6 W | 8 W |
| Environment | Operating Temperature and Humidity | Temperature 59°F to 86°F (15°C to 30°C) Humidity: 30% to 80% RH | | | |
| | Storage Temperature and Humidity | Temperature 32°F to 95°F (15°C to 35°C) Humidity: 10% to 80% RH | | | |
| Daily Duty Cycle | | 4,000 pages | | | |
| Additional Features | | End User Replaceable Feeder Rollers, Electronic Color Dropout (Red, Green, Blue) | | | |
| Additional Contents | | Power Cord, USB Cable, Roller Cleaning Paper, CD-ROM (Installation and Operation Manual, VRS, User Utility Software), Printed Documents (Quick Installation Guide and Warranty Card) | | | |
| Bundled Software | | Scanning Capture Software: scan to PDF, file, retrieve, publish, e-mail, and adjust all your documents with the touch of a button (included in US models only) | | | |
| Consumables Options | | Roller Exchange Kit S005503 Roller Cleaning Kit S005504 | | Roller Exchange Kit S005503 Roller Cleaning Kit S005504 Pre-scan Front-page Imprinter Kit 0123060 Ink Cartridge S005506 | |

*Paper lengths larger than legal size are supported to 25 inches. A resolution of less than 300 dpi and single sheet feeding is recommended.

© 2006 Bowe Bell+Howell Scanners, L.L.C. All rights reserved. BÖWE BELL+HOWELL and the Böwe Bell+Howell logo are trademarks or registered trademarks of BBH, Inc. VirtualReScan, Capio and the VRS logo are registered trademarks of Kofax Imaging Products, Inc. All other trademarks and service marks are the property of their respective owners. Specifications are subject to change without notice.

Phone: 1.800.SCAN.494 or 1.847.675.7600 www.bbhscanners.com Form #SD-193-A rev. 09/06

