

# intimus<sup>®</sup> 602

A MARTIN YALE BRAND



## Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

## Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

## Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



**5.8 mm  
Strips**

## Cutting mechanism is insensitive to

Paper clips	yes
CDs / DVDs	yes
3.5" floppy disks	no
Credit cards	yes
Passports	yes

## Performances intimus 602

Size of shreds	5.8 mm
Shredding capacity*	27 - 29 sheets
Security level DIN 32757	level 2
Working width	405 mm
Cutting speed	0.25 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Dimensions W / D / H	66/43/102 cm
Weight	60 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.  
Technical changes and colour variances reserved. 1/2004



# intimus® 602

A MARTIN YALE BRAND



## Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

## Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

## Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel



**3.8 mm  
Strips**

## Cutting mechanism is insensitive to

Paper clips	yes
CDs / DVDs	yes
3.5" floppy disks	no
Credit cards	no
Passports	no



## Performances intimus 602

Size of shreds	3.8 mm
Shredding capacity*	23 - 25 sheets
Security level DIN 32757	level 2
Working width	405 mm
Cutting speed	0.14 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Dimensions W / D / H	66/43/102 cm
Weight	60 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.  
Technical changes and colour variances reserved. 1/2004

# intimus<sup>®</sup> 602 CC

A MARTIN YALE BRAND



**3.8 x 36 mm  
Cross Cut**

## Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

## Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

## Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

## Cutting mechanism is insensitive to

Paper clips	yes
CDs / DVDs	no
3.5" floppy disks	no
Credit cards	yes
Passports	no



## Performances intimus 602 CC

Size of shreds	3.8 x 36 mm
Shredding capacity*	20 - 22 sheets
Security level DIN 32757	level 3
Working width	405 mm
Cutting speed	0.14 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Dimensions W / D / H	66/43/102 cm
Weight	60 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.  
Technical changes and colour variances reserved. 1/2004

# intimus<sup>®</sup> 602 CC

A MARTIN YALE BRAND



**1.9 x 15 mm  
Cross Cut**

## Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

## Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

## Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

## Cutting mechanism is insensitive to

Paper clips	yes
CDs / DVDs	no
3.5" floppy disks	no
Credit cards	no
Passports	no

## Performances intimus 602 CC

Size of shreds	1.9 x 15 mm
Shredding capacity*	14 - 16 sheets
Security level DIN 32757	level 4
Working width	405 mm
Cutting speed	0.14 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Dimensions W / D / H	66/43/102 cm
Weight	60 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.  
Technical changes and colour variances reserved. 1/2004



# intimus<sup>®</sup> 602 HS

A MARTIN YALE BRAND



0.8 x 12 mm  
Cross Cut

## Operation

- On / off control automatic, via light barrier
- Cutout by autoreverse when overloaded and reversed

## Equipment

- "Ready" indicator
- LEDs for paper jam, bin full or door open
- Dustproof enclosure - mounted on rollers for flexible use
- Large shelf - hinged to save space
- Large-volume catchbasket with changeable, environmentally acceptable PE bag

## Technical features

- Electronics controlled by micro-controller
- Cutters made of solid, hardened special steel

## Cutting mechanism is insensitive to

Paper clips	no
CDs / DVDs	no
3.5" floppy disks	no
Credit cards	no
Passports	no



## Performances intimus 602 HS

Size of shreds	0.8 x 12 mm
Shredding capacity*	8 - 10 sheets
Security level DIN 32757	level 5
Working width	405 mm
Cutting speed	0.14 m/sec.
Catchbasket / Volume	130 l
Noise level	54 dB(A)
Dimensions W / D / H	66/43/102 cm
Weight	60 kg

\* based on 70g/m<sup>2</sup> DIN A4 paper. Sheet capacities vary depending on quality, weight, grain of paper and sufficient power supply.  
Technical changes and colour variances reserved. 1/2004