

P-150

Portable scanner.

you can

Introducing an ultra-compact duplex scanner for SOHO users and mobile executives. Meet the industry's smallest, fastest and most portable A4 duplex scanner: the P-150 from Canon.



Great in the office and on the move.

An ultra-compact design and easy USB-based power makes it ideal for users in the office, on the road or at home.

A real productivity driver.

With duplex scanning up to 30ipm and a large 20-sheet automatic document feeder, the innovative P-150 dramatically speeds processing.

Flexible and user-friendly.

The cutting edge modern design of the P-150 with its ease-of-use and unique built-in CaptureOnTouch Lite software for one-touch scanning delivers true plug-and-scan flexibility and simplicity.

Revolutionary features and benefits include:

- Speedy USB-powered duplex scanning up to 15ppm / 30ipm
- Ultra-compact and easy to carry
- True plug-and-scan with built-in CaptureOnTouch Lite software
- Class-leading with 20-sheet automatic feeder
- Superb colour image quality
- Money-saving energy efficiency
- Stylish black-silk finish design
- TWAIN and ISIS driver for flexible connectivity
- Powerful OCR processing for fast keyword searching
- Multi-platform use on PC, Mac and Linux


imageFORMULA


product
design
award
2010

Canon

Specifications: imageFORMULA P-150 scanner

| | | |
|---|---|------------------|
| Type | Desktop Type Sheet Fed Scanner | |
| Document Reading Sensor | CMOS CIS 3 Line Sensor | |
| Optical Resolution | 600dpi | |
| Light Source | RGB LED | |
| Reading Sides | Front / Back / Duplex | |
| Interface | High Speed USB 2.0 | |
| Dimensions | Tray Closed: 280 (W) x 95 (D) x 40 (H) mm Tray Opened: 280 (W) x 222.7 (D) x 202.2 (H) mm | |
| Weight | Approx. 970g | |
| Power Requirements | USB Cable Only: 5VDC, 0.5A USB Cable and Power Supply: USB Cable 5VDC, 1A Using Optional AC Power Adaptor 6VDC, 0.8A | |
| Power Consumption | Scanning: 5W (2 USB cables), 2.5W (1 USB cable) Sleep Mode: 1W Power Turned Off: 0.1W | |
| Operating Environment | 10 - 32.5°C (50 - 90.5°F), Humidity: 20 - 80% RH | |
| Environmental Compliance | RoHS and ENERGY STAR | |
| READING SPEED * (200dpi, Portrait, A4)** | With 2 USB Cable / AC Adaptor | With 1 USB Cable |
| B & W | 15ppm / 30ipm | 12ppm / 14ipm |
| Greyscale | 15ppm / 30ipm | 12ppm / 14ipm |
| Colour | 10ppm / 20ipm | 10ppm / 10ipm |
| DOCUMENT SPECIFICATIONS | 50.8 - 216mm | |
| Width | 70 - 256mm | |
| Length | Automatic Feeding – 52 - 128g/m ² (0.06 - 0.15mm) | |
| Thickness | (Embossed Card / Thick Card Scanning Not Supported) | |
| Paper Separation | Separation Pad | |
| Feeder Capacity | 20 sheets (64g/m ²) | |
| OUTPUT Resolution | 150 x 150dpi, 200 x 200dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi | |
| Mode | Black and White, Error Diffusion, Advanced Text Enhancement (II), 256-level Grayscale (8-bit), 24-bit Colour, Auto Colour Detection | |

| | |
|--|---|
| PRODUCT FEATURES | Deskew, Auto Page Size Detection, Double Feed Detection (by Length), Skip Blank Page, Text Orientation Recognition, Colour Dropout (RGB) / Enhancement (Red), Moiré Reduction, Edge Enhancement, Preset Gamma Curve, Prescan, Scan Area Setting, Prevent Bleed Through / Remove Background, Separate Front & Back Settings, Continuous Scanning |
| BUNDLED SOFTWARE | For Windows ISIS / TWAIN Drivers for Windows 2000 / XP PRO / Vista / 7, CaptureOnTouch, CaptureOnTouch Lite (Built-in), Nuance PaperPort, Presto! BizCard Reader |
| | For MAC OS X*** TWAIN Driver for Mac, CaptureOnTouch |
| Options | AC Power Adaptor, Soft Carrying Case |
| Consumables | Separation Pad, Feed Roller Unit |
| Suggested Daily Duty Cycle | Approx. 500 scans / day |
| <p>* Actual scanning speed may vary depending on your system configuration and PC specification ** The P-150 is capable of the same scanning speeds at 300dpi when scanning in B&W and Greyscale *** Supports Mac OS X 10.4.11 - 10.6.3 or later Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and / or product names are trademarks and / or registered trademarks of their respective manufacturers in their markets and / or countries.</p> | |



Canon Electronics Inc
www.canon.com

Canon Europe
www.canon-europe.com

European Edition
© Canon Europe 2010 (0000)

Canon Ireland
Arena Road,
Sandyford Industrial Estate
Dublin 18, Ireland
T: 01 2052400
F: 01 2958141
www.canon.ie

Canon (UK) Ltd
Woodhatch
Reigate
Surrey
RH2 8BF
Telephone No: 01737 220000
Facsimile No: 01737 220022
www.canon.co.uk