

www.fujitsu-europe.com



ScanPartner 620C A4 document scanner

- 7ppm Colour at 200dpi
- 20ppm Mono at 200dpi
- Simplex scanner
- 50 page ADF & Flatbed
- A7 – A4 scanning

FUJITSU

THE POSSIBILITIES ARE INFINITE



Fujitsu's ScanPartner 620C is the latest addition to the ScanPartner range offering high speed, high quality scanning to the low volume workgroup market.

The ScanPartner 620C offers users the ability to scan at up to 20 pages per minute in black and white at 200dpi or 7 pages per minute in full 36-bit single pass colour (R,G,B) and at a resolution of up to 600 x 1200 dpi that easily satisfies optical character recognition. Long life cold cathode lighting, single pass CCD scanning, and the high resolution provide high quality scanning of colour or black and white documents for use in an array of applications.

The ScanPartner 620C has the capability to scan up to a size of A4 through the ADF from a minimum size of A7 or 1" x 1" on the flatbed which provides added versatility.

The ScanPartner 620C offers a MTBF of up to 5,000 hours based on 500 documents per day and has an industry standard SCSI-2 interface that support all Twain and ISIS compliant applications and are supported by leading Document Imaging Software products. Like all Fujitsu scanners the scanpartner range has been designed to deliver the highest level of image quality, reliability, performance and compatibility.

620C Specifications

Operating method		Flatbed and ADF (automatic document feeder)
Image sensor		CDD (charge-coupled device)
Light source		Cold Cathode fluorescent lamp
Document size	Minimum	A7 (74 mm x 105 mm)
	Maximum	A4 (210 mm x 297 mm)
Output resolution		Up to 600 x 1200 dpi (1% increments)
Optical resolution	ADF	600 dpi
	Flatbed	600 dpi
Scanning speed	Colour	7 ppm for A4 portrait format at 200 dpi
	Mono	20 ppm for A4 portrait format at 200 dpi
Grayscale level	(internal)	256 levels
Halftone patterns		Dither; Error diffusion
Capacity of ADF		Maximum 50 sheets, paper weight: 64 g/m ² , A4
Interface		SCSI-2
Video output format		Binary, Grayscale, (256 levels), 36 bit colour
Power requirements		100 to 240v (international), 47/63Hz
Power consumption		<30 watts
Operating environment		Temperature: 5°C - 35°C (41°F-95°F)
Relative humidity		10% - 85% (non-condensing)
Dimensions (WxDxH)		570 x 350 x 166 mm
Weight		10 kg
Recommended daily throughput		500 pages (5,000 hours MTBF)

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative.

Fujitsu Europe Limited

Hayes Park Central
Hayes End Road
Hayes Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643

Fujitsu Italia S.p.A.

Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201

Fujitsu France S.A

1, place des Etats-Unis
Silic 310
94588 Rungis cedex
France
Tel: (+33-(0)1) 41 80 38 88
Fax: (+33-(0)1) 41 80 38 50

Fujitsu Deutschland GmbH

Frankfurter Ring 211
80807 München
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100

Fujitsu Nordic AB

Kung Hans väg 12
SE-192 68 Sollentuna
Sweden
Tel: (+46-(0)8) 626 45 00
Fax: (+46-(0)8) 626 45 88

